

FRITZ 114

Outdoor Lighting




Your product advantages

- ✓ **Award Winning Design:** IF Design Award
- ✓ **Versatile:** Applicable for technical as well as for decorative lightings
- ✓ **Sustainable:** Tool-less change of electronic and LED modules
- ✓ **Reliable:** Lifetime of the LED driver and LED module at 85,000 h


Application areas

Traffic roads, roads in residential areas

Dimensions (mm)



Light distribution (asymmetric wide beam)



FRITZ 114

Basic

Eco

Lighting fixtures body		
Material	Die cast aluminium	
Colour (powder coating)	RAL or DB	
Mounting type	Post top mounting (Ø 76 / 60 mm)	
Orientation possibilities	Basic up tilt of 0°	
Dimension (length x width x height)	830 x 340 x 320 mm	
Weight	app. 10 kg	
Exposed wind surface	0.14 m²	
IP Protection class	IP 65	
Glass type	PMMA	
Shock resistance	IK 08	
Photometric properties		
Light source	LED-Modules with High-Power-LED	
Optical system	Asymmetric wide beam light distribution	
Rated luminous flux	1,300 / 2,000 / 2,600 / 3,200 lm	1,000 - 3,200 lm
Light efficiency	105 lm/W	105 lm/W
Colour temperature	3,000 / 4,300 K	
Colour rendering index (Ra)	> 70	
Dimming (power control)	—	Power line control / Digital
Rated lifetime at (ta) 30C°	80,000 h at L80/B10	85,000 h at L80/B10
Temperature management	—	✓
Constant Light Output (CLO)	—	✓
Electrical properties		
Rated power	12 / 18 / 24 / 30 W	10 – 30 W (in 2W-steps)
Electrical protection class	Class I / II	
Rated voltage	198 – 264 V	120 – 277 V
Frequence	50 – 60 Hz	
Surge protection (L-N / L N-ground)	6 kV	6 / 8 kV
Installation suggestions		
Application areas	Traffic roads, roads in residential areas	
Light point height	3,5 – 6 m	
Lighting classes	ME/S	
Admitted ambient temperature (ta)	-25°C – +35°C	
Other properties		
Certificate	CE	
Connection to circuit breaker (B16)	17 pcs.	
Options		
Additional part over-tension resistant	10 kV	
Side mounting piece for Ø 60, 42x100 mm	✓	
Angle fixation through extension bracket	1.5°	
DALI Interface (not at power line control)	—	✓

04/2016_TDS_EN_V1.0

HELLUX International GmbH

Mergenthalerstraße 6
30880 Laatzen, Germany

Phone +49 (0)511 820 10-0
Fax +49 (0)511 820 10-102

info@hellux.de
www.hellux.de

©HELLUX International GmbH. Data may vary due to actual version. Subject to technical changes. All statements without guarantee.



A COMPANY OF **WÜNSCHE GROUP**